EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1	"4810018".pn.	US-PGPUB; USPAT; EPO; JPO	OR	ON	2009/03/30 12:34
L2	11	("4727647" | "4729713").PN. OR ("4810018"). URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/30 12:34
L3	5	shozo near3 kadota.in. and insert$3 with component and correct$3 with lead	US-PGPUB; USPAT; EPO; JPO	OR	ON	2009/03/30 12:38
L4	0	kazuaki near3 kosaka.in. and insert$3 with component and correct$3 with lead not 3	US-PGPUB; USPAT; EPO; JPO	OR	ON	2009/03/30 12:40
L5	0	minoru near3 kitani.in. and insert $3 with component and correct$3 with lead not 3	US-PGPUB; USPAT; EPO; JPO	OR	ON	2009/03/30 12:40
L6	1	((lead wire pin leg post terminal) with (electronic electrical) near2 (part device element component) and (print$3 wiring circuit) near2 (board substrate) and (urg$4 grip$4 hold$3 grasp$4 press$4 push$3) with (pressure force magnitude) with (control$4 monitor$3 measur	US-PGPUB; USPAT; EPO; JPO	OR	ON	2009/03/30 12:42

		$3 detect$3) and (correct$3 straighten$4) near4 (lead wire pin leg post terminal)).clm.					
L7	27	("4165557" | "4212075" | "4286379" | "4292727" | "4309808" | "4356619" | "4464829" | "4557043" | "4574462" | "4590660" | "4622740" | "4627157" | "4745679" | "4749141").PN. OR ("5165165"). URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2009/03/30 12:43
L8	4	((lead wire pin leg post terminal) with (electronic electrical) near2 (part device element component) and (print$3 wiring circuit) near2 (board substrate) and (urg$4 grip$4 hold$3 grasp$4 press$4 push$3) with (control$4 monitor$3 measur $3 detect$3) and (correct$3 straighten$4) near4 (lead wire pin leg post terminal)).clm. not 6	US-PGPUB; USPAT; EPO; JPO	OR	ON	2009/03/30 12:46

S70	3	(lead wire pin leg) with (electronic electrical) near2 (part device element component) and (print$3 wiring circuit) near2 (board substrate) and (urg$4 grip$4 hold$3 grasp$4 press$4 push$3) with (pressure force magnitude) with (control$4 monitor$3 measur $3 detect$3) and (electronic electrical) near2 (part device element component) with (deformation deform$3 rigid$3 hardness) and (correct$3 straighten$4) near4 (lead wire pin leg)	US-PGPUB; USPAT; EPO; JPO	OR		ON		2009/03/26 17:23
S71	6	("4907628" | "4957146").PN. OR ("5078186"). URPN.	US-PGPUB; USPAT; USOCR	OR		ON		2009/03/26 17:25
S72	8	("3769823" | "3796201").PN. OR ("4907628"). URPN.	US-PGPUB; USPAT; USOCR	OR		ON		2009/03/26 17:26
S73	12	("4064917" | "4103718" | "4590660" | "4644633" | "4868978" | "4907628" | "4941248" | "5105857").PN. OR ("5222528"). URPN.	US-PGPUB; USPAT; USOCR	OR		ON		2009/03/26 17:31

| S74 | 4 | ("4907628" \| "5078186" \| "5477894").PN. OR ("5806571").URPN. | US-PGPUB; USPAT; USOCR | OR | | ON | 2009/03/26 17:32 |

3/30/09 12:48:11 PM
C:\ Documents and Settings\ dnguyen21\ My Documents\ EAST\ Workspaces
\ 10521754 EC insertg lead wire.wsp